





















PRODUCT	APPLICATION		DIRECTIONS FOR USE	DILUTION	SAFETY	PPE
XPOLY8 Size: 5L Code: 240004 	Hard Floor Stripper Liquefies and suspends old sealer coats in a liquid emulsion, which is easily removed with an autoscrubber or a mop & bucket		<ol style="list-style-type: none"> 1. Add recommended amount of XPOLY8 to cold water 2. Apply liberally to the floor 3. Allow to work for 3 to 5 minutes, being sure to keep the floor wet 4. In most situations it is advisable to wet-scrub the floor using a black pad on an autoscrubber or by using a low speed machine with a black pad. 5. Pick-up the dissolved sealer with an autoscrubber or mop and bucket. 6. Rinse the floor with clean water. Allow the floor to dry before applying sealer. <p>XPOLY8 can be used on vinyl, vinyl asbestos, rubber, no-wax linoleum, lino tile, marble, terrazzo, ceramic quarry tiles and most types of flooring.</p>	Moderate buildup: (125ml per L) Heavy buildup: (250ml per L)	Harmful if swallowed. Harmful if inhaled. May cause skin irritation. Avoid contact with eyes. pH 14	 
IMPACT Size: 5L Code: 090056 	Base Floor Sealer Seals any type of flooring: terrazzo, vinyl, tiles, timber, stone, ceramic, terracotta, granite, cement, pavers, stencilled concrete in preparation for a gloss polish coat		<p>Preparation:</p> <ol style="list-style-type: none"> 1. Remove old finish. Apply floor stripper then wet-scrub with a black pad 2. Pick up excess with clean water in a mop and bucket or an autoscrubber <p>Application:</p> <ol style="list-style-type: none"> 1. Dry-burnish floor before applying sealer 2. Add IMPACT to a clean bucket. Use <u>neat</u> 3. Immerse polycotton sealing mop in solution then wring lightly 4. Mop should be wet but not dripping 5. Apply solution to floor in overlapping Figure-of-8 strokes 6. Allow to dry 7. Apply 2 to 3 coats (wait 30 mins between coats) 8. Buff after final coat <p>Maintenance:</p> <ol style="list-style-type: none"> 1. Damp mop floor daily with neutral detergent 	Ready To Use (RTU) Use undiluted	No hazardous ingredients. Avoid contact with eyes. pH 9.5	 
THERMAGLO PLUS Size: 5L Code: 200127 	High Gloss Sealer Seals any type of flooring: terrazzo, vinyl, tiles, timber Low speed burnishing: excellent results at speeds from 250rpm to 2,000rpm High slip-resistance: Exceeds Australian Standard significantly		<p>Preparation:</p> <ol style="list-style-type: none"> 1. Remove old finish 2. Apply base sealer. Then choose THERMAGLO PLUS or BRILLIANCE as top coat <p>Application:</p> <ol style="list-style-type: none"> 1. Dry-burnish floor before applying sealer 2. Add THERMAGLO PLUS to a clean bucket. Use <u>neat</u> 3. Immerse polycotton sealing mop in solution then wring lightly 4. Mop should be wet but not dripping 5. Apply solution to floor in overlapping Figure-of-8 strokes 6. Allow to dry 7. Apply 2 to 3 coats (wait 30 mins between coats) 8. Buff after final coat <p>Maintenance:</p> <ol style="list-style-type: none"> 1. Damp mop floor daily with neutral detergent 2. Mop or use autoscrubber weekly with GLOKLEEN or REJUVEN8 maintainer 	Ready To Use (RTU) Use undiluted	No hazardous ingredients. Avoid contact with eyes. pH 9	 
BRILLIANCE Size: 5L Code: 020408 	Ultra High Gloss Sealer Seals any type of flooring: terrazzo, vinyl, tiles, slate High speed burnishing: excellent results at speeds at or above 1,000rpm High slip-resistance: Exceeds Australian Standard significantly		<p>Preparation:</p> <ol style="list-style-type: none"> 1. Remove old finish 2. Apply base sealer. Then choose THERMAGLO PLUS or BRILLIANCE as top coat <p>Application:</p> <ol style="list-style-type: none"> 1. Dry-burnish floor before applying sealer 2. Add BRILLIANCE to a clean bucket. Use <u>neat</u> 3. Immerse polycotton sealing mop in solution then wring lightly 4. Mop should be wet but not dripping 5. Apply solution to floor in overlapping Figure-of-8 strokes 6. Allow to dry 7. Apply 2 to 3 coats (wait 30 mins between coats) 8. Buff after final coat <p>Maintenance:</p> <ol style="list-style-type: none"> 1. Damp mop floor daily with neutral detergent 2. Mop or use autoscrubber monthly with a maintainer 	Ready To Use (RTU) Use undiluted	No hazardous ingredients. Avoid contact with eyes. pH 9.5	 
PROTECT Size: 5L Code: 190634 	Matte Outdoor Sealer Seals footpaths, driveways, stencilled concrete, sandstone, granite, marble, slate, brick and tiles		<p>Preparation:</p> <ol style="list-style-type: none"> 1. Clean with 200207 TILE PLUS (16ml/L) 2. No need for a base sealer when using PROTECT <p>Application:</p> <ol style="list-style-type: none"> 1. Add PROTECT to a clean bucket. Use <u>neat</u> 2. 1L will cover 20 m 3. Immerse polycotton sealing mop in solution then wring lightly 4. Mop should be wet but not dripping 5. Apply solution to floor in overlapping Figure-of-8 strokes 6. Allow to dry 7. Apply 2 to 3 coats (wait 30 mins between coats) 8. Allow 24 hours to cure <p>Maintenance:</p> <ol style="list-style-type: none"> 1. Garden hose spray with water or damp mop floor daily with neutral detergent 	Ready To Use (RTU) Use undiluted	No hazardous ingredients. Avoid contact with eyes. pH 8.5	 

CAUTION – UNDER NO CIRCUMSTANCES ARE CHEMICALS TO BE MIXED – REFER TO SDS FOR FURTHER INFORMATION

If you have any questions, please contact Whiteley on 1800 833 566

For online information, please visit www.whiteley.com.au

Stripping Floors

1. Remove loose soil and debris from floor.
2. Choose **XPOLY8** (*diluted at 125-250ml per litre of water*).
3. Apply liberally to the floor.
4. Allow to work for 3 to 5 minutes, being sure to keep the floor wet.
5. If the stripper dries the floor will need to be re-stripped, so do small sections in turn.
6. Wet-scrub the floor using a black pad on a low speed machine.
7. Pick-up the dissolved sealer with an autoscrubber or mop and bucket.
8. Rinse floor with clean water and allow the floor to dry before applying the sealer.



Sealing Floors

1. Dry-burnish floor before applying sealer to ensure debris is removed.
2. Add **IMPACT** priming base sealer to a clean bucket.
3. Immerse a new polycotton sealing mop in the sealer then wring lightly.
4. Mop should be wet but not dripping.
5. Apply **IMPACT** to floor in overlapping Figure-of-8 strokes.
6. Apply 2-3 coats of **IMPACT**. Allow 30 mins between coats. Buff final coat.
7. Add **THERMAGLO PLUS** or **BRILLIANCE** to a clean bucket.
8. Immerse a new polycotton sealing mop in the sealer then wring lightly.
9. Apply **THERMAGLO PLUS** or **BRILLIANCE** to floor in overlapping Figure-of-8 strokes.
10. Apply 2-3 coats. Allow 30 mins between coats. Buff final coat.



Maintaining Floors

1. Daily:
 - a) Sweep or damp mop to remove loose debris.
 - b) Mop floor with a neutral detergent or disinfectant.
 - c) **TEMPO HD** is chemically compatible with **THERMAGLO PLUS** and **BRILLIANCE**.
2. Monthly:
 - a) Apply **GLOKLEEN** or **REJUVEN8** maintainer.
 - b) Use either a mop and bucket or an autoscrubber.
 - c) Buff dry.
3. Tiles & Concrete in Kitchens, Bathrooms and Outdoor Areas:
 - a) Clean floor daily with a neutral detergent or disinfectant
 - b) Deep clean monthly with **TILE PLUS** heavy duty alkaline detergent

