TASKI



TASKI[®] swingo XP-R B BMS Battery Powered Stand on Scrubber Drier

Large battery powered stand on

swingo XP-R Kit 4

CODE	
D7523416ANZ-KIT4	1 x TASKI swingo XP-R B BMS
	4 x Battery traction 6V, 180Ah
	2 x Standard scrubbing brush 38 cm

swingo XP-R Kit 5

CODE	
D7523416ANZ-KIT5	1 x TASKI swingo XP-R B BMS
	4 x Battery traction 6V, 180Ah
	2 x Pad drive harpoon grip 38 cm

swingo XP-R Kit 6

CODE	
D7523416ANZ-KIT6	1 x TASKI swingo XP-R B BMS
	4 x Battery traction 6V, 180Ah
	2 x Standard scrubbing brush 38 cm
	2 x Pad drive harpoon grip 38 cm

swingo XP-R Optional Accessories

CODE	
D7514962	Battery traction 6V, 180Ah
D7522220	Pad drive harpoon grip 38 cm
D7522221	Standard scrubbing brush 38 cm
D7522222	Scrubbing brush washed concrete 38 cm
D7522223	Scrubbing brush abrasive 38 cm
D7523342	Scrubbing brush water saving 38 cm
D7523390	TASKI intelliTrail hardware
D7516242	TASK intelliDose XP-R
D6093762	TASKI intellipad - 15 inch (38cm)

Productivity Extended

The XP-R is a battery operated scrubber driers which performs with unsurpassed agility offering the manoeuvrability of a much smaller machine and unbeatable cleaning performance. With total 360 degrees visibility around the machine and a larger solution tank both lead to increased productivity up to 10%.

Next Generation Technology

Next generation electronics and software providing best-in-class driving experience. The XP-R is compatible with TASKI intelliTrail intelligent GPS fleet tracking system. It's rugged, ergonomic design maintains a professional image.

Ease of Maintenance and Safety

Yellow maintenance points for easy everyday maintenance and automatic cut out if operator steps off machine leads to excellent cleaning and drying results for safe floors.

Direct Savings

Reduced water and energy consumption compared to standard scrubbers. TASKI swingo XP-R is engineered for sustainability through conservative use of water, chemicals and energy use.



Technical data	
Theoretical performance	4,500 m²/h
Working width	75 cm
Squeegee width	95 cm
Solution tank (nominal)	113 L
Recovery tank (nominal)	140 L
Rated voltage	24 V
Battery capacity	180 Ah/C5
Battery autonomy (nominal)	3.25 hours
Machine weight ready for use w/240Ah batteries, 75 kg driver	452 kg
Dimensions (L x W x H) (height above driver's seat)	1310 x 950 x 1300 mm
Door pass through width	80 cm
Brush system	2 x 38 cm
Brush pressure	0.13 - 0.25 N/cm ²
Cleaning speed/ transportation speed	6 km/h
Sound level	69dB(A)