


Dyson backplate technical specification



HU
03

Front elevation

All dimensions shown in mm (+/-5 mm)
Not to scale



See table for recommended mounting heights



Recommended installation heights from floor	
Male	Y 1451 mm
Female	Y 1416 mm
Wheelchair user	Y 1207 mm
Child 5-8	Y 1079 mm
Child 8-11	Y 1179 mm
Child 11-14	Y 1256 mm
Dyson backplate dimensions	
Height 991 mm Width 575 mm Depth 5 mm	

Minimum clearance above machine	
	210 mm
Rear cable entry point from floor	
Male	1293 mm
Female	1258 mm
Wheelchair user	1049 mm
Child 5-8	921 mm
Child 8-11	1021 mm
Child 11-14	1098 mm

For further information please contact Dyson

AU: 1800 426 337
 aucommercial@dyson.com
 www.dyson.com.au

NZ: 0800 397 667
 nzcommercial@dyson.com
 www.dyson.co.nz

Installing the Dyson backplate

Where only unsupported plasterboard is available for installation, a Dyson backplate must be used. Fixing to unsupported plasterboard (drywall) without the aid of a Dyson backplate will not result in safe and secure installation for your machine, and may also invalidate your guarantee.

If the wall you are fixing the machine to has an airgap, the fixings used must be of a sufficient length to provide a secure installation. Do not use sealant when attaching the machine to the wall.

The Dyson backplate helps protect the wall from water damage and can be used to cover holes/marks left from previously installed products – including the Dyson Airblade dB hand dryer.

Contact the Dyson Helpline for further information.

Construction

Stainless steel (brushed)

Back plate mounting bracket: Stainless steel – Brushed (304L)

Logistics

Net weight: 6.7 kg / 14.7 lbs

Packaged weight: 11.10 kg / 24.47 lbs

Packaged dimensions:

(H) 71 × (W) 664 × (D) 1295 mm

Standard guarantee

5 year guarantee



For further information please contact Dyson

AU: 1800 426 337
aucommercial@dyson.com
www.dyson.com

NZ: 0800 397 667
nzcommercial@dyson.com
www.dyson.co.nz